

## TIME DISTRIBUTION

*Slave Clocks with aluminium housing - indoor operation by master clock*



- Sizes  $\varnothing$  230, 300 and 400 mm.
- Housing of anodised aluminium.
- Black numerals or hour marks on white background. Black hours- and minutes hand. Convex protection glass.
- Single sided, depth of housing 36 mm., for surface mounting. Fixing to wall or ceiling (hanging) also possible by additional bracket.
- For double sided installation two clocks and one bracket are used.
- Clocks with only hours- and minutes hand are operated by 24 V polarised 1/1-min. impulses from master clock.
- Clocks with stepping seconds hand (red) - almost soundless by oil damper - are operated by 24 V polarised 1/1-sec. impulses from master clock.

Further models are described in separate brochures.

### *Brackets (wall/ceiling)*

- for double sided installation or single sided together with a back side cover.
- of anodised aluminium with adjustable arm for setting of the distance to wall or ceiling.

## SINGLE SIDED

Size of dial in mm.	Type of dial A = numerals H = hour marks	Art.No.	
		1/1-min. *)	1/1-sec.**)
230	A	111002-00	111200-00
230	H	111006-00	111201-00
300	A	111014-00	111202-00
300	H	111018-00	111203-00
400	A	111026-00	111204-00
400	H	111030-00	111205-00

\*) = sweeping hours hand, stepping minutes hand

\*\*\*) = sweeping hours- and minutes hand, stepping seconds hand

## DOUBLE SIDED

Size of dial in mm.	Type of dial A = numerals H = hour marks	Art.No.	
		1/1-min. *)	1/1-sec. **)
230	A	111082-00	111210-00
230	H	111086-00	111211-00
300	A	111094-00	111212-00
300	H	111098-00	111213-00
400	A	111106-00	111214-00
400	H	111110-00	111215-00

Technical specifications available on separate sheet.