

## Impulse Clocks

### *Water protected IP65 Slave Clocks from WESTERSTRAND*



## **HORIZON IP65**

dia. 300 and 500 mm.,  
case of grey acrylic plastic



**Horizon Clocks** are developed considering the tough environment in food industry. Single sided dia. 300 and 500 mm. Double sided dia. 500 mm.

# HORIZON IP65



Dial face type H - marks dia. 300mm.



Dial face type A - numerals dia. 500 mm.

## Technical data:

Operation method	Size	Dial type	Single sided (artnr)	Double sided (artnr)
Minute impulse	Ø 300 mm	A	5131120-00	
Minute impulse	Ø 300 mm	H	5133120-00	
Minute impulse	Ø 500 mm	A	5151120-00	5451120-00
Minute impulse	Ø 500 mm	H	5153120-00	5453120-00
Timecode	Ø 300 mm	A	5131520-00	
Timecode	Ø 300 mm	H	5133520-00	
Timecode	Ø 500 mm	A	5151520-00	5451520-00
Timecode	Ø 500 mm	H	5153520-00	5453520-00

Viewing distance:

Dia. 300 mm. = 12 metres

Dia. 500 mm. = 40 metres

Dial face:

White with black numerals (type A) or marks (type H)

Hands:

Black hour- and minute hands

Case/Protection cover:

Acrylic plastic, colour RAL 7037/transparent

Operation method:

- Minute impulse

24VDC polar reversing 1/1-min.impulses from Master Clock.

- Timecode

Hard wired from Master Clock.

Other impulse systems on request.

Montage:

Single sided surface wall mounting.

Double sided wall- or ceiling mounting.

Pole mounting installation device available as option.

Ambient temperature:

-20°C up to +50°C

Relative humidity:

Max. 85%

Weight:

Ø 300 mm. single sided = 2,0 kgs

Ø 500 mm. single sided = 4,4 kgs

Ø 500mm. double sided = 7,0 kgs

Protection class:

IP65.

We reserve the right to make changes at any time.